

**Technical details:**

- sturdy drill body, PCD tipped
- flat peak design with double bevel for tear-free blind holes
- shank with clamping flat and length adjusting screw

Application:

- for drilling blind - and through holes
- perfect machining on nesting machines
- especially applicable for abrasive workpiece materials
- for use on CNC machines and on throughfeed drilling-machines

Workpiece materials:

- cement bounded and fire resistant board materials
- fibre-reinforced synthetic materials (FVK)
- HPL (TRESPA®, laminate, RESOPAL®)
- multiplex
- laminated chipboard and MDF

PCD Dowel Drills

PCD Dowel Drills Z2

D [mm]	L ₂ [mm]	L ₄ [mm]	L ₁ [mm]	S [mm]	Part-No.	
8	27	2,6	57,5	10	30540-9-08025-L	●
8	27	2,6	57,5	10	30540-9-08025-R	●
8	35	2,6	70	10	30540-9-08035-L	●
8	35	2,6	70	10	30540-9-08035-R	●
10	35	3,2	70	10	30540-9-10035-L	●
10	35	3,2	70	10	30540-9-10035-R	●
12	35	3,9	70	10	30540-9-12035-L	●
12	35	3,9	70	10	30540-9-12035-R	●

Accessories: Length adjusting screw

M 5 x 8	39075-0-05080-R	●
M 5 x 17 mm for quick change adaptor	39075-0-05017-R	●

● Popular size, ex stock ○ While stocks last